Mark-up of Proposed Text Amendment to Zoning Bylaw 12800

Black Font Existing Text in Zoning Bylaw 12800

Strikethrough: Proposed deletion from Zoning Bylaw 12800

<u>Underline:</u> Proposed addition to Zoning Bylaw 12800

55. Landscaping

55.3 General Planting Requirements

- 1. Unless otherwise specified in this Bylaw, Landscaping shall be provided in accordance with the following:
 - e. all open space including Front Yards, Rear Yards, Side Yards and Yards, at Grade Amenity Areas, Private Outdoor Amenity Areas, Setback areas and Separation Spaces shall be landscaped with flower beds, grass, ground cover or suitable decorative hardscaping in addition to trees and shrubs. This requirement shall not apply to those areas designated for parking or vehicular circulation.
 - f. Notwithstanding subsection 55.3(1)(e), for Industrial Uses on Sites Abutting a Transportation/Utility Corridor, Calgary Trail N.W., Gateway Boulevard N.W., Sherwood Park Freeway N.W., Stony Plain Road N.W., or Yellowhead Trail N.W., all required trees may be located in the Front Yard and the Yard Abutting the roadway specified, for the purpose of screening.

55.5 General Requirements

12. For Industrial Uses on Sites that are unserviced at the time of application, a minimum of 50% of plant materials shall be native to the Edmonton area.

Rationale

This provision provides the opportunity for trees be concentrated in the front yard and the yard abutting the major corridor for industrial properties abutting these corridors is proposed.

In order to improve the survival rate of plantings on unserviced lots, a requirement is added for 50% of landscaping on unserviced industrial sites to be native to the Edmonton area.

Page 1 of 4 Report: CR_3823

57. General Performance Standards

57.1 General Performance Standards for Industrial Developments

Any development or Site used for any Permitted or Discretionary Use in the <u>AGI</u>. IB, IL, IM or IH Zones shall comply with the performance standards of this Section.

- 1. Any Use or activity in the IB or IL Zones shall comply with the following standards:
 - c. all loading, service, trash collection and Accessory storage areas, and trucking yards shall be located to the rear or sides of the principal building, and shall be screened from view from any public roadway other than a Lane, and from adjacent Sites, by building walls, <u>freestanding walls</u>, landscape materials, berms, <u>wood</u> Fences or a combination of these;
 - d. <u>Except for landscape materials, screening materials shall have a maximum height</u> of 3.7 m;

(Renumber the rest of Section 57.1(1) accordingly)

- 2. Any Use or activity in the IM or IH Zones, or any Use other than Rural Farms in the AGI Zone, shall comply with the following appearance standards:
 - c. all outdoor service, assembly, trash collection and storage areas including the trucking yards associated with such activities shall be screened from view from any public roadway other than a Lane, and from adjacent Sites, <u>by building walls</u>, <u>freestanding walls</u>, <u>landscape materials</u>, <u>berms</u>, <u>wood Fences or a combination of these</u>, unless the public roadway is a local road serving only Sites in an <u>AGI</u>. IM or IH Zone, or the adjacent Site is Zoned <u>AGI</u>. IM or IH;
 - d. <u>Except for landscape materials, screening materials shall have a maximum height</u> of 3.7 m:

General Performance Standards are applied to AGI land, excluding rural farms, so as to improve the aesthetic quality of development on these sites.

Additional specificity is added to the general performance standards to clarify what constitutes acceptable screening from public roadways and adjacent sites.

A maximum height of 3.7 m (approximately 12 ft) is introduced for screening materials.

Page 2 of 4 Report: CR_3823

(Renumber the rest of Section 57.1(2) accordingly)

57.2 General Performance Standards for Temporary Storage

- 1. Any Temporary Storage Use shall be screened from view from any public roadway other than a Lane, and from adjacent Sites, by building walls, freestanding walls, landscape materials, berms, wood Fences or a combination of these.
- 2. Except for landscape materials, screening materials shall have a maximum height of 3.7 m.

(Renumber the rest of Section 57 accordingly)

420 (IM) Medium Industrial Zone

420.4 Development Regulations for Permitted and Discretionary Uses

- 4. The maximum building Height shall be 18.0 m.
- 5. For Lots Abutting a Transportation/Utility Corridor, Calgary Trail N.W., Gateway Boulevard N.W., Sherwood Park Freeway N.W., Stony Plain Road N.W., or Yellowhead Trail N.W., materials and equipment in an outdoor storage area, including shipping containers, or outdoor displays shall have:
 - a. <u>a maximum Height of 8.0 m, measured from Grade to the highest point of the materials or display, within 15 m of the Lot Line Abutting the roadway specified above: and</u>
 - b. a maximum Height of 2.0 m, measured from Grade to the highest point of the materials or display, within 6.0 m of the Lot Line Abutting the roadway specified above.

(Renumber the rest of Section 420 accordingly)

Screening requirements for all temporary storage are added so that they can be applied to Direct Control Zones in addition to standard Industrial Zones.

The maximum height applies to all structures and materials.

Lower maximum heights for outdoor storage in the IM zone are added for sites abutting a major corridor in order to ensure that storage items are less visible from the specified roadways. The proposed regulation creates a gradual height transition for storage at different distances from the property line.

Page 3 of 4 Report: CR_3823

430 (IH) Heavy Industrial Zone

430.4 Development Regulations for Permitted and Discretionary Uses

5. The maximum building Height shall be 30.0 m.

630 (AGI) Industrial Reserve Zone

630.4 Development Regulations for Permitted and Discretionary Uses

- 5. Height is not restricted for Buildings or structures for Agricultural and Natural Resource Development Uses. Excluding buildings or structures for Agricultural and Natural Resource Development Uses, the maximum building Height shall not exceed 10.0 m, in accordance with Section 52.
- 6. For Lots Abutting a Transportation/Utility Corridor, Calgary Trail N.W., Gateway Boulevard N.W., Sherwood Park Freeway N.W., Stony Plain Road N.W., or Yellowhead Trail N.W., materials and equipment in an outdoor storage area, including shipping containers, or outdoor displays shall have:
 - a. <u>a maximum Height of 8.0 m, measured from Grade to the highest point of the materials or display, within 15 m of the Lot Line Abutting the roadway specified above.</u>

(Renumber the rest of Section 630 accordingly)

The maximum height applies to all structures and materials.

The maximum height applies to all structures and materials.

Lower maximum heights for outdoor storage in the AGI zone are added for sites abutting a major corridor in order to ensure that storage items are less visible from the specified roadways. The proposed regulation creates a gradual height transition for storage at different distances from the property line.

Page 4 of 4 Report: CR_3823